IGL COATINGS™ ECOCOAT ELIXIR

Material no.

Specification 154368 Revision date 11.08.2023

Version **1.00** Page 1 of 6



1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME : IGL Coatings™ Ecocoat Elixir

FUNCTION : Hydro- & oleophobizing and easy clean agent surface modifier and gloss enhancer

COMPANY : Ominent Sdn Bhd

ADDRESS : No.7, Jalan Majistret U1/26, Hicom-Glenmarie Industrial Park, Seksyen U1, 40150 Shah Alam,

Selangor.

PHONE : +60355690980

EMAIL ADDRESS : regulations@iglcoatings.com

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Physical hazards

Flammable liquid Category 4

Health hazards

Aspiration Toxicity Category 2

2.2 Label Elements

Regulation (EC) No. 1272/2008



GHS08

Signal word

Danger

Hazard statements

H227 Combustible Liquid

H304 May be fatal if swallowed and enters airways

Precautionary statements

P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.
P280 Wear protective gloves, protective clothing, eye protection and face mask.
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P370+P378 In case of fire: Use Water mist, Extinguishing powder, Alcohol-resistant foam, Carbon dioxide,

Sand.

P405 Store locked up.

P403+P233+P235 Store in a well-ventilated place. Keep container tightly closed. Keep cool.

P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance

with applicable laws and regulations, and product characteristics at time of disposal.

2.3 Other Hazards

Inhalation of vapour may damage health. Product hydrolyses, producing Methanol (CAS no. 67-56-1). Methanol is highly flammable.

IGL COATINGS™ ECOCOAT ELIXIR

Material no.

Specification 154368 Revision date 11.08.2023

Version **1.00** Page 2 of 6



3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS No.	Chemical Name				
	EC No.	Index No.	REACH	No.	
	Classification according				
63148-62-9	Polydimethylsiloxane				
	613-156-5	Not applicable	Not ap	plicable	
	Not Available				
64742-47-8	Distillates (petroleum),	30-50%			
	265-149-8	Not applicable	Not applicable		
	Flam. Liq. 4; H227: Asp. Tox. 1: H304				
5593-70-4	Titanium tetrabutanolate				
	227-006-8	Not applicable		Not applicable	
	Flam. Liq. 4; H227				

4. FIRST AID MEASURES

4.1 Description of first aid measures

General Information

Take person to a safe place. Observe self-protection for first aid.

After Inhalation

Keep the patient calm. If unconscious place in stable sideways position. Protect against loss of body heat. In cases of sickness, seek medical advice.

After skin contact

Remove contaminated or soaked clothing. Immediately rinse with plenty of soap and water.

In the event of a visible skin change or other complaints, seek medical advice.

After contact with eyes

Rinse immediately with plenty of water for 10-15 minutes. Remove contact lenses, if presence and easy to do. Seek medical advice in case of continuous irritation.

After ingestion

If conscious, give several small portions of water to drink. Do not induce vomiting.

Seek medical advice immediately and clearly identify substance.

4.2 Most important symptoms and effects, both acute and delayed

Any relevant information can be found in other parts of this section.

4.3 Indication of any immediate medical attention and special treatment needed

In case of contact with water materials splits off (also in gastrointestinal tract) methanol in larger amounts; therefore consider poisoning on methanol and also observe known period of latency of several days.

5. FIRE-FIGHTING MEASURES

5.1 Suitable extinguishing media

Water mist, dry powder, alcohol resistant foam, carbon dioxide, sand.

5.2 Unsuitable extinguishing media

Water spray and water jet

5.3 Special hazards arising from the substance or mixture

No data available.

5.4 Advise for firefighters

Use respiratory protection independent of recirculated air.

5.5 Unusual Fire Hazards:

Not known.

. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment (refer to section 8). Keep unprotected person away. Avoid contact with skin and eyes. Avoid inhaling mists and vapours.

IGL COATINGS™ ECOCOAT ELIXIR

Material no.

Specification 154368 Revision date 11.08.2023

Version **1.00** Page 3 of 6



If material is released indicate risk of slipping.

6.2 Environmental precautions

Prevent material from entering surface waters, drains or sews and soil.

Contain any fluid that runs out using suitable material (e.g. earth).

Retain contaminated water/extinguishing water.

Dispose of in prescribed marked containers.

6.3. Methods and material for containment and cleaning up

Do not flush away with water.

For small amounts: Absorb with a liquid binding material such as diatomaceous earth and dispose of according to local/state/federal regulations.

Contain larger amounts and pump up into suitable containers. Clean any slippery coating that remains using a detergent/soap solution or another biodegradable cleaner. Exhaust vapours.

6.4 Reference to other sections

Safe handling: Refer to section 7.

Personal protection equipment: Refer to section 8.

Disposal: Refer to section 13.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Advice on safe handling

Wear personal protection equipment (Refer to section 8).

Avoid inhalation of vapour or mist.

Keep away from sources of ignition – No smoking.

Take measures to prevent the build-up of electrostatic charge.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Moisture sensitive.

Advice on storage compatibility

Do not store together with food and feeding stuffs.

Further information on storage conditions

Keep the packing dry and well-sealed to prevent contamination.

7.3 Specific end use(s): Refer to section 1.

8. EXPOSURE CONTROL/PERSONAL PROTECTION

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

Component	CAS No.	Value	Control parameter	
Methanol (Hydrolysis	67-56-1	TWA	200 ppm	
product)			260 mmg/m ³	

8.2 Exposure Control

8.2.1 General protective and hygienic measures:

Wash hands before breaks and at the end of work. Do not inhale gases/vapours/aerosols.

Do not eat, drink or smoke when handling.

8.2.2 Personal protective equipment:

Respiratory protection:

In case of long or strong exposure: gas mask filter ABEK.

Protection of hands:

Using gloves made from butyl rubber. Gloves suitable for up to 60 minutes' use. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

Eye protection: Tight fitting protective goggles.

Skin protection: Protective clothing.

8.3 Exposure to the environment limited and controlled:

IGL COATINGS™ ECOCOAT ELIXIR

Material no.

Specification 154368 Revision date 11.08.2023 Version

4 of 6

1.00 Page

Prevent material from entering surface waters and soil.

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point : 180 °C

Density : 0.972 g/cm³ at 25 °C

Flash Point : 71 °C (ISO3679: Closed cup)

: Not applicable На : Virtually insoluble Solubility in Water

Appearance (colour) : Colourless Appearance (form) : Liquid Odour : Peculiar

10. STABILITY AND REACTIVITY

10.1 Reactivity: Not classified as a reactivity hazard.

10.2 Chemical stability: Stable under normal condition.

Thermal decomposition / conditions to avoid: No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions: No data available.
- **10.4 Conditions to avoid**: Moisture, heat, open flame and other sources of ignition.
- **10.5 Incompatible materials**: Oxidizing agents, acid and water.
- 10.6 Hazardous decomposition products: When heated to temperature above 150°C (300F) in the presence of air, product can form formaldehyde vapours. Hazardous decomposition products will be formed upon contact with water and humid air.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects: No data available.

Acute toxicity: No data available.

Skin corrosion/irritation: No data available.

Serious eye damage/eye irritation: No data available Respiratory or skin sensitization: No data available.

Summary of evaluation of the CMR properties: No data available. Specific target organ toxicity - single exposure: No data available. Specific target organ toxicity – repeated exposure: No data available.

Aspiration hazard: May be fatal if swallowed and enters airways

12. ECOLOGICAL INFORMATION

12.1 Toxicity

No data available.

12.2 Process of degradability

No data available.

12.3 Bioaccumulative potential

No data available.

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB Assessment

No data available.

12.6 Other adverse effects

No data available.

13. DISPOSAL CONSIDERATION

13.1 Waste treatment methods

Material:

Recommendation:

Dispose of according to regulations by incineration in a special waste incinerator.



IGL COATINGS™ ECOCOAT ELIXIR

Material no.

 Specification
 154368
 Revision date
 11.08.2023

 Version
 1.00
 Page
 5 of 6



Observe local/state/ federal regulations.

Uncleaned packaging:

Recommendation:

Completely discharge containers (no tear drops, no powder rest, scraped carefully).

Containers may be recycled or re-used. Observe local/state/ federal regulations.

Dispose of contents/container in accordance with local/regional/national/international regulation.

Sewage disposal-related information

Do not empty into drains.

13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

14. TRANSPORT INFORMATION

14.1 IATA-DGR

UN number : -

UN proper shipping name : Non dangerous goods

Transport hazard class(es) : Packing group : Environmental hazards : -

Special precautions for user : No data available.

14.2 IMDG-Code

UN number : -

UN proper shipping name : Non dangerous goods

Transport hazard class(es) : Packing group : Environmental hazards : -

Special precautions for user : No data available.

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture US Federal Regulations

US. Toxic Substances Control Act (TSCA)

All chemical substances in this material are included on the TSCA Inventory of Chemical Substances.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) Hazardous Substance List

(Hydrolysis product) Methanol (67-56-1) - RQ 5000 lbs

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Emergency Planning and Community Right-To-Know Act (EPCRA) Section 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

Emergency Planning and Community Right-To-Know Act (EPCRA) Section 313 Toxics Release Inventory (TRI) Reporting

(Hydrolysis product) Methanol (67-56-1)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CRF 68.130)

None present or none present in regulated quantities.

US. State Regulation

US. California Proposition 65

⚠ Warning: This product can expose you to chemicals including methanol, which is known to the State of California to cause developmental toxicity. For more information, go to www.P65Warnings.ca.gov

IGL COATINGS™ ECOCOAT ELIXIR

Material no.

Specification 154368 Revision date 11.08.2023

Version **1.00** Page 6 of 6



EU Regulation

EU. Directive 2012/18/EU (SEVESO III) on Major Accident Hazards Involving Dangerous Substances, Annex I:

Not applicable.

15.2. Chemical safety assessment

No chemical safety assessment is required for this product.

16. OTHER INFORMATION

Further information

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material use in combination with any other materials or any process, unless specified in the test.