SAFETY DATA IGL COATINGS™ E Material no.	_	igl coatings		
Specification Version	154321 1.15	Revision date Page	16.02.2021 1 of 7	
1. IDENTIFICATIO PRODUCT NAM FUNCTION COMPANY ADDRESS PHONE EMAIL ADDRESS	E : IGL C : Adhe : Omir : No.7, Selar : +603	oatings™ ecoclean glu sive and glue remover nent Sdn Bhd Jalan Majistret U1/26,	off Hicom-Glenmarie In	DMPANY/UNDERTAKING dustrial Park, Seksyen U1, 40150 Shah Alam,

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture	
Regulation (EC) No. 1272/2008	
Physical hazards	
Flammable liquid	Category 3
Health hazards	
Eye Irritation	Category 2
Skin Irritation	Category 2
Acute toxicity (Inhalation)	Category 4
Specific Target Organ Toxicity – Single Exposure	Category 3

2.2 Label Elements

Regulation (EC) No. 1272/2008



Signal word

Danger Hazard statements

H226	Flammable liquid and vapour
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P233 Keep container tightly closed.
- P235 Keep cool.
- P240 Ground and bond container and receiving equipment.
- P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
- P242 Use non-sparking tools.
- P243 Take action to prevent static discharges.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264 Wash exposed skin thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P302+P352 IF ON SKIN: Wash with plenty of water.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water (or shower).
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P312 Call a POISON CENTRE/doctor if you feel unwell.



Specification Version	154321 1.15	Revision date Page	16.02.2021 2 of 7		
P332+P313	lf ski	n irritation occurs: Get	medical advice/attention.		
P337+P313	lf eye	If eye irritation persists: Get medical advice/attention.			
P362+P364	Take	Take off contaminated clothing and wash it before reuse.			
P370+P378	In ca	In case of fire: Use fire extinguisher to extinguish.			
P403+P233	Store in a well-ventilated place. Keep container tightly closed.				
P403+P235	5 Store in a well-ventilated place. Keep cool.				
P405	Store locked up.				
P501	Dispo	ose of contents/conta	iner to comply with local, state and federal regulations.		

(¿) igl coatings™

3. **COMPOSITION/INFORMATION ON INGREDIENTS**

CAS No.	Chemical Name			Quantity	
	EC No.	Index No.	REACH No.		
	Classification accor	Classification according to Regulation (EC) No. 1272/2008 (CLP)			
7732-18-5	Water			30-60%	
	231-791-2	Not applicable	Not applicable		
	Not applicable				
67-63-0	Isopropyl alcohol			10-30%	
	200-661-7	603-117-00-0	Not Applicable		
	Eye Irrit. 2: H319; Fl	am. Liq. 2: H225; STOT	SE 3: H336		
67784-80-9	Methyl soyate			10-30%	
	267-055-2	Not applicable	Not applicable		
	Not applicable				
111-76-2	Butyl cellosolve			1-5%	
	203-905-0	603-014-00-0	01-2119475108-36-0000		
	Acute Tox. 4: H302;	Acute Tox. 4: H302; Skin Irr. 2: H315; Eye Irr. 2: H319			
9005-64-5	Polysorbate 20			1-5%	
	500-018-3	Not applicable	01-2119971749-17-0001		
	Not applicable	Not applicable			
10043-35-3	Boric acid			<0.1%	
	233-139-2	Not applicable	01-2119486683-25-0000		
	Repr. 1B: H360				
7447-40-7	Potassium chloride			<0.1%	
	231-211-8	Not applicable	01-2119539416-36-0001		
	Not applicable				
6834-92-0	Sodium Metasilicat	e		<0.1%	
	229-912-9	Not applicable	01-2119449811-37-0000		
	Skin Corr. 1B: H314				

Additional information:

The exact percentage of some ingredients used in this product are considered to be proprietary and are withheld as confidential business information.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General Information

Take off contaminated clothing.

After Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

After skin contact

Wash skin with soap and water. Do not apply neutralizing agents.

Get medical attention if irritation develops and persists.

After contact with eyes

Rinse immediately with plenty of water for at least 15 minutes.

Material no.

Specification	154321	Revision date	16.02.2021
Version	1.15	Page	3 of 7

Remove contact lenses, if presence and easy to do. Get medical attention if irritation develops and persists. **After ingestion**

igl coatings

Rinse mouth with water. Immediately after ingestion: give lots of water to drink. Do not induce vomiting. Get medical attention immediately.

Ingestion of large quantities: immediately to hospital. Doctor: Gastric lavage.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation

Coughing, dry/sore throat, dizziness, headache and narcosis.

Symptoms/effects after skin contact

Dry skin.

Symptoms/effects after eye contact

Irritation of eye tissue.

Symptoms/effects after ingestion

AFTER ABSORPTION OF LARGE QUANTITIES:

Central nervous system depression. Headache. Dilation of the blood vessels. Low arterial pressure. Nausea. Vomiting. Abdominal pain. Disturbed motor response. Disturbances of consciousness.

FOLLOWING SYMPTOMS MAY APPEAR LATER: Body temperature fall. Slowing respiration.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

5.1 Suitable extinguishing media

Water spray, alcohol-resistant foam, polyvalent foam, BC powder and carbon dioxide (CO₂).

5.2 Unsuitable extinguishing media

Solid water jet ineffective as extinguishing medium.

5.3 Special hazards arising from the substance or mixture

Fire hazard:

DIRECT FIRE HAZARD. Highly flammable. Gas/vapor flammable with air within explosion limits.

INDIRECT FIRE HAZARD. May be ignited by sparks. Gas/vapor spreads at floor level: ignition hazard.

Explosion hazard:

DIRECT EXPLOSION HAZARD. Gas/vapour explosive with air within explosion limits.

INDIRECT EXPLOSION HAZARD. May be ignited by sparks.

Reactivity:

Upon combustion: CO and CO₂ are formed. Violent to explosive reaction with (strong) oxidizers. Prolonged storage/in large quantities: may form peroxides.

5.4 Special firefighting procedure

Move container from fire area if you can do so without risk. Water runoff can cause environmental damage.

5.5 Advise for firefighters

Cool tanks/drums with water spray/remove them into safety. Do not move the load if exposed to heat. Firefighters must use standard protective equipment including flame retardant coat, helmet, gloves, rubber boots, and self-contained breathing apparatus.

5.6 Unusual Fire Hazards:

Not known.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained. Stop engines and no smoking. No naked flames or sparks. Sparks- and explosion-proof appliances and lighting equipment. Keep container closed. Wash contaminated clothes. Wear personal protection equipment (Refer to section 8).

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

6.3 Methods and material for containment and cleaning up

Material no. S

Specification	154321	Revision date	16.02.2021
Version	1.15	Page	4 of 7

Large spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas.

igl coatings

Small spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

6.4 Reference to other sections

Safe handling: Refer to section 7 Personal protection equipment: Refer to section 8 Disposal: Refer to section 13

HANDLING AND STORAGE 7.

7.1 Precautions for safe handling

Advice on safe handling

Wear personal protection equipment (Refer to section 8).

Use care in handling/storage. Avoid release to the environment. Do not empty into drain. Do not breathe the mist or vapor. Provide adequate ventilation. Keep away from naked flame/heat. Keep away from ignition sources/sparks.

Advice on protection against fire and explosion

No information available.

Further information on handling

General protection and hygiene measures: Refer to section 8.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, dry place out of direct sunlight.

Advice on storage compatibility

Do not store together with food and feeding stuffs.

Further information on storage conditions

Recommended storage temperature: 20-25°C.

7.3 Specific end use(s): Refer to section 1.

EXPOSURE CONTROL/PERSONAL PROTECTION 8.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace: Specified substance: Isopropyl alcohol

specified substance.		
ACGIH	ACGIH TWA	200 ppm (2-propanol; USA; Time-weighted average exposure limit 8 hrs; TLV-Adopted value)
ACGIH	ACGIH STEL	400 ppm (2-propanol; USA; Short time value; TLV- Adopted value)
OSHA	OSHA PEL (TWA)	980 mg/m ³
OSHA	OSHA PEL (TWA)	400 ppm

8.2 Exposure Control

8.2.1 General protective and hygienic measures:

Wash hands before breaks and immediately after handling the product with mild soap and water. Wash contaminated clothes before reuse.

Handle in accordance with good industrial hygiene and safety practice.

8.2.2 Personal protective equipment:

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment (gas mask with filter type A). **Protection of hands:**

Wear protective gloves.

Eye protection: Safety glasses/goggles with side shields.

Skin and body protection: Wear suitable protective clothing.

Material no.

Specification	154321	Revision date	16.02.2021
Version	1.15	Page	5 of 7

9.	PHYSICAL AND CHEMICAL PRO	PERTIES
	Boiling point	: 95 °C
	Density	: 0.96 g/cm ³
	Melting point	: Not applicable
	Flash point	: 26 °C
	рН	: 13.0
	Evaporation rate	: 1.957 (butyl acetate =1)
	Solubility in water	: Soluble
	Appearance (colour)	: Clear Yellow
	Appearance (form)	: Liquid
	Odour	: Citrus

10. STABILITY AND REACTIVITY

10.1 Reactivity: Upon combustion: CO and CO₂ are formed. Explosive reaction with strong oxidizing agents.

10.2 Chemical stability: Stable at normal condition.

10.3 Possibility of hazardous reactions: No additional information available.

10.4 Conditions to avoid: Direct sunlight, heat, high temperature, incompatible materials, open flame and sparks.

🕜 igl coatings

10.5 Incompatible materials: Strong oxidizing agents.

10.6 Hazardous decomposition products: Carbon monoxide (CO) and carbon dioxide (CO₂).

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Exposure route	Endpoint	Value	Species	Source
Oral	LD50	10385 mg/kg	Rat	ECHA
Inhalation	LC50	18.8 mg/L	Rat	ECHA
Dermal	LD50	5944.8 mg/kg	Rabbit	ECHA

Skin corrosion/irritation: May causes mild skin irritation.

Eye irritation: May causes eye irritation.

Respiratory or skin sensitization: Shall not be classified as respiratory or skin sensitization.

Summary of evaluation of the CMR properties: Shall not be classified as a germ cell mutagenic, carcinogenic nor as a reproductive toxicant.

Specific target organ toxicity – single exposure: May causes drowsiness or dizziness.

Specific target organ toxicity – repeated exposure: No data available.

Aspiration hazard: No data available.

12. ECOLOGICAL INFORMATION

12.1 Aquatic Toxicity

Specified substance: Isopropyl alcohol

Endpoint	Value	Species	Exposure time	Source
LC50	9.64 g/L	Freshwater fish	4 days	ECHA
EC50/LC50	10 g/L	Aquatic Invertebrates	24 hours	ECHA
EC10 or NOEC	1.8 g/L	Freshwater algae	7 days	ECHA

Specified substance: Butyl Cellosolve

Endpoint	Value	Species	Exposure time	Source
LC50	1474 mg/L	Freshwater fish	96 hours	ECHA
LC50	1250 mg/L	Marine water fish	96 hours	ECHA
NOEC	100 mg/L	Fish	14 days	ECHA
EC50	1550 - 1800 mg/L	Aquatic invertebrates	48 hours	ECHA
EC10/LC10 or NOEC	100 mg/L	Aquatic invertebrates	-	ECHA

Material no. Specification

Version

154321	Revision date
1.15	Page

16.02.2021 6 of 7

Endpoint	Value	Species	Exposure time	Source
LL50	100 mg/L	Fish	96 hours	ECHA
NOELR	10 mg/L	Aquatic invertebrates	21 days	ECHA
EL50	23.9 mg/L			
EL10	7.47 – 19.05 mg/L	Aquatic algae and cyanobacteria	72 hours	ECHA
EL50	20.24 – 58.84 mg/L			

12.2 Process of degradability

Readily biodegradable.

12.3 Bioaccumulative potential No data available.

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB Assessment

The substance is not PBT/vPvB.

12.6 Other adverse effects

No data available.

13. DISPOSAL CONSIDERATION

13.1 Waste treatment methods

Recycle by distillation. Remove to an authorized waste incinerator for solvents with energy recovery.

Sewage disposal-related information

Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals.

13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

13.3 Remarks

Do not discharge into surface water. Obtain the consent of pollution control authorities before discharging to wastewater treatment plants. Please consider the relevant national or regional provisions.

14. TRANSPORT INFORMATION

14.1 IATA-DGR

UN number	: 1263
UN proper shipping name	: Paint related materials
Transport hazard class(es)	: 3
Packing group	: 111
Environmental hazards	: No
Special precautions for user	: No data available.
Remarks	:-
14.2 IMDG-Code	
UN number	: 1263
UN proper shipping name	: Paint related materials
Transport hazard class(es)	: 3
Packing group	: 111
Environmental hazards	: No
Marine pollutant	: No

Material no.

Specification	154321	Revision date
Version	1.15	Page

EmS Code

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture US Federal Regulations

US. Toxic Substances Control Act (TSCA)

: -

All chemical substances in this material are included on the TSCA Inventory of Chemical Substances.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) Hazardous Substance List

16.02.2021 7 of 7 🕜 igl coatings

None present or none present in regulated quantities.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Emergency Planning and Community Right-To-Know Act (EPCRA) Section 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

Emergency Planning and Community Right-To-Know Act (EPCRA) Section 313 Toxics Release Inventory (TRI) Reporting

Component	CAS No.
Isopropyl alcohol	67-63-0

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CRF 68.130)

None present or none present in regulated quantities.

US. State Regulation

US. California Proposition 65

No ingredient requiring a warning under CA Prop 65.

EU Regulation

EU. Directive 2012/18/EU (SEVESO III) on Major Accident Hazards Involving Dangerous Substances, Annex I:

Not applicable.

15.2 Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

16. OTHER INFORMATION

Further information

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material use in combination with any other materials or any process, unless specified in the test.