

# SAFETY DATA SHEET

## IGL COATINGS™ ECOCOAT WINDOW E1



Material no.

Specification

154287

Revision date

16.02.2021

Version

1.15

Page

1 of 6

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME : IGL Coatings™ ecocoat window E1  
FUNCTION : Hydro- & oleophobic and easy clean agent surface modifier for glass and glazed ceramic  
COMPANY : Ominent Sdn Bhd  
ADDRESS : No.7, Jalan Majistret U1/26, Hicom-Glenmarie Industrial Park, Seksyen U1, 40150 Shah Alam, Selangor.  
PHONE : +60355690980  
EMAIL ADDRESS : regulations@iglcoatings.com

### 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

Regulation (EC) No. 1272/2008

##### Physical hazards

Flammable liquids Category 2

##### Health hazards

Specific Target Organ Toxicity- Repeated Exposure Category 2

#### 2.2 Label Elements

Regulation (EC) No. 1272/2008



GHS02



GHS08

##### Signal word

Danger

##### Hazard statements

H225 Highly flammable liquid and vapour

H373 May cause damage to organs through prolonged or repeated exposure

##### Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233 Keep container tightly closed.

P235 Keep cool.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P260 Do not breathe mist or vapours.

P280 Wear protective gloves, protective clothing, eye protection and face mask.

P314 Get medical advice/attention if you feel unwell.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P370+P378 In case of fire: Use alcohol resistant foam, carbon dioxide or dry chemical to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents in accordance with local/regional/federal regulations.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS No.	Chemical Name			Quantity
	EC No.	Index No.	REACH No.	
	Classification according to Regulation (EC) No. 1272/2008 (CLP)			
64-17-5	Ethanol			70-90%
	200-578-6	603-002-00-5	01-2119457610-43-0000	
	Flam. Liq. 2: H225			
998-30-1	Triethoxysilane			10-20%
	213-650-7	Not applicable	Not applicable	

# SAFETY DATA SHEET

## IGL COATINGS™ ECOCOAT WINDOW E1

Material no.

Specification

154287

Revision date

16.02.2021

Version

1.15

Page

2 of 6



STOT RE 3: H373

### Additional information:

The exact percentage of some ingredients used in this product are considered to be proprietary and are withheld as confidential business information.

## 4. FIRST AID MEASURES

### 4.1 Description of first aid measures

#### General Information

Remove contaminated or saturated clothing.

#### After Inhalation

Following the inhalation of aerosols or mist: Move victims to fresh air.

If symptoms persist, consult a physician for treatment.

#### After skin contact

Wash off immediately with plenty of water. Consult a doctor in the event of permanent skin irritation.

#### After contact with eyes

Keeping eyelid open, immediately rinse thoroughly for at least 15 minutes using plenty of water or if necessary, eye rinsing solution. Remove contact lenses, if presence and easy to do

In case of persistent discomfort: Consult an ophthalmologist.

#### After ingestion

Have the mouth rinse with water. Have patient drink plenty of water in small sips. Obtain medical attention.

### 4.2 Most important symptoms and effects, both acute and delayed

No information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

If required, therapy of irritative effect.

After absorbing large amounts of substance: administration of activated charcoal.

Acceleration of gastrointestinal passage

## 5. FIRE-FIGHTING MEASURES

### 5.1 Suitable extinguishing media

Water spray, fog, alcohol resistant foam, CO<sub>2</sub> or dry chemical.

### 5.2 Unsuitable extinguishing media

No data available.

### 5.3 Special hazards arising from the substance or mixture

Possible formation of fluorine-containing fumes.

In case of fire cool endangered containers with water.

Closed container may rupture if strongly heated.

### 5.4 Advise for firefighters

Water used to extinguish fire should not enter drainage systems, soil or stretches of water.

Ensure there are sufficient retaining facilities for water used to extinguish fire.

Fire residues and contaminated fire extinguishing water must be disposed of on accordance with local regulations.

In case of fire: Wear a self-contained respiratory apparatus.

### 5.5 Unusual Fire Hazards:

None.

## 6. ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment (Refer to section 8). Ensure adequate ventilation.

### 6.2 Environmental precautions

Do not allow entrance in sewage water, soil stretches of water, groundwater and drainage systems.

### 6.3 Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Fill into marked, sealable containers. To be disposed of in compliance with existing regulation.

Suitable absorbents: diatomaceous earth universal absorbent.

### 6.4 Reference to other sections

# SAFETY DATA SHEET

## IGL COATINGS™ ECOCOAT WINDOW E1

Material no.

Specification

154287

Revision date

16.02.2021

Version

1.15

Page

3 of 6



Safe handling: Refer to section 7

Personal protection equipment: Refer to section 8

Disposal: Refer to section 13

## 7. HANDLING AND STORAGE

### 7.1. Precautions for safe handling

Provide good ventilation or extraction. Avoid contact with skin and eyes. Handle in accordance with good industrial hygiene and safety practice. The personal protective equipment used must meet the requirements of Regulation (EU) 2016/425 and amendments (CE certification). If workplace exposure limits are exceeded and/or larger amounts are released (leakage, spilling, dust) the indicated respiratory protection should be used. If there is the possibility of skin/eye/body protection should be used. Do not breathe in vapours or aerosols.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Advice on protection against fire and explosion

Take precautionary measures against static charges, keep away from sources of ignition.

Danger of explosion from residual product fumes; avoid spark production through cutting, grinding, or welding work in the area of the container.

#### Requirements for storage rooms and vessels

Keep containers tightly closed in a cool, well-ventilated place. Protect from moisture.

Recommended storage temperature: 20-25°C.

### 7.3. Specific end use(s):

The product is not supposed to be used in spray applications which are intended for the end consumer. If the substance can be applied to spraying products in the end-consumer market, a separate risk assessment of the finished end-product will have to be performed. If a substance for spray applications is supposed to be applied at the site of the end customer, please ask for technical information.

## 8. EXPOSURE CONTROL/PERSONAL PROTECTION

### 8.1 Control parameters

#### Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

**Additional Information:** The lists valid during the making were used as basis.

### 8.2 Exposure Control

#### 8.2.1 General protective and hygienic measures:

Wash hands before breaks and at the end of work. Ensure adequate ventilation.

#### 8.2.2 Personal protective equipment:

##### Respiratory protection

In case of dusts/vapours/aerosols being formed or if the limit values like TLV are exceeded: use respiratory equipment with suitable filter (filter type ABEK) or wear a self-contained respiratory apparatus. Use only respiratory protection equipment with CE-symbol including four-digit test number. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used. Note time limit for wearing respiratory protective equipment.

##### Hand protection

Glove material : Butyl-rubber

Break through time : >= 480 min

Glove material : Fluorinated rubber (Viton)

Break through time : >= 480 min

Additional information: Selection of protective gloves to meet the requirements of specific workplaces. Suitability for specific workplaces should be clarified with protective glove manufacturers. The information is based on our own tests, references from the literature and information from glove manufacturers, or derived by analogy with similar materials. Please observe that the daily duration of usage of a chemical protective glove is in practice far shorter due to the many influencing factors (e.g. temperature, mechanical strain on the glove material) than the permeation time determined acc. EN 374.

##### Eye protection

# SAFETY DATA SHEET

## IGL COATINGS™ ECOCOAT WINDOW E1

Material no.

Specification

154287

Revision date

16.02.2021

Version

1.15

Page

4 of 6



Safety glasses

### Skin and body protection

Suitable protective clothing - Use disposable clothing if appropriate.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point	: 78 °C (Tested substance: Ethanol)
Melting Point	: No data available.
Flash Point	: 7 °C
Evaporation Rate	: No data available.
Flammability Limit-Lower	: 3.5 % (V) Tested substance: Ethanol
Flammability Limit-Upper	: 28 % (V) Tested substance: Ethanol
Vapour pressure	: 60 hPa (20 °C) Tested substance: Ethanol <0.1 hPa (20 °C) Tested substance: pure substance
Density	: 0.8 g/cm <sup>3</sup> (20 °C)
pH	: 7.2 (1000g/l) (20 °C)
Solubility in Water	: Miscible
Appearance (colour)	: Colourless
Appearance (form)	: Liquid
Odour	: Alcohol

## 10. STABILITY AND REACTIVITY

**10.1 Reactivity:** No dangerous reaction known under conditions of normal use.

**10.2 Chemical stability:** Stable under recommended storage conditions.

Thermal decomposition / conditions to avoid: No decomposition if used according to specifications.

**10.3 Possibility of hazardous reactions:** Reacts violently with strong oxidants.

**10.4 Conditions to avoid:** Keep away from heat, open flames and other ignition sources.

**10.5 Incompatible materials:** Strong oxidising agents

**10.6 Hazardous decomposition products:** None known.

## 11. TOXICOLOGICAL INFORMATION

### Information on toxicological effects

Exposure route	Endpoint	Value	Species	Sources
Oral	LD50	6311.8 mg/kg	Rat	ECHA
Inhalation	LC50	124.85 mg/L	Rat	ECHA
Dermal	LD50	2000 mg/kg	Rat	ECHA

**Skin corrosion/irritation:** No data available.

#### Specified substances:

Ethanol : OECD Test Guideline 404 (Rabbit): Not irritating

Triethoxysilane : OECD Test Guideline 404 (Rabbit): Not irritating

**Eye irritation:** No data available.

#### Specified substances:

Ethanol : (Rabbit) Not irritating

**Respiratory or skin sensitization:** No data available.

#### Specified substances:

Ethanol : Local Lymph Node Assay, OECD TG 429 (Mouse): Non sensitizing, Not classified.

Triethoxysilane : Buehler Test, OECD Test Guideline 406 (Guinea Pig): Not a skin sensitizer.

**Summary of evaluation of the CMR properties:** No data available.

**Specific target organ toxicity – single exposure:** No data available.

**Specific target organ toxicity – repeated exposure:** No data available.

**Aspiration hazard:** No data available.

## 12. ECOLOGICAL INFORMATION

### 12.1 Toxicity

# SAFETY DATA SHEET

## IGL COATINGS™ ECOCOAT WINDOW E1

Material no.

Specification

154287

Revision date

16.02.2021

Version

1.15

Page

5 of 6



### Specified substance: Ethanol

Endpoint	Value	Species	Exposure time	Sources
LC50	11.2 – 14.2 g/L	Freshwater fish	96 hours	ECHA
EC10/LC10 or NOEC	250 mg/L	Freshwater fish	5 days	ECHA
EC50	5.012 g/L	Freshwater invertebrates	48 hours	ECHA
EC10/LC10 or NOEC	9.6 mg/L	Freshwater invertebrates	10 days	ECHA
EC50	275 mg/L	Freshwater algae	96 hours	ECHA

### 12.2 Process of degradability

No data available.

### 12.3 Bioaccumulative potential

No data available.

### 12.4 Mobility in soil

No data available.

### 12.5 Results of PBT and vPvB Assessment

Data are not available.

### 12.6 Other adverse effects

An expert judgement stated that no classification is necessary based on present knowledge.

## 13. DISPOSAL CONSIDERATION

### 13.1 Waste treatment methods

With respect to local regulations, e.g. dispose to suitable waste incineration plant.

#### Uncleaned packaging

Do not reuse empty containers and dispose of in accordance with the regulations issued by the appropriate local authorities.

Incorrect disposal or reuse of this container is illegal and can be dangerous.

If there is product residue in the emptied container, follow directions for handling on the container's label.

Other countries: observe the national regulations.

### 13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

### 13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

## 14. TRANSPORT INFORMATION

### 14.1 IATA-DGR

UN number : 1263  
UN proper shipping name : Paint-related materials  
Transport hazard class(es) : 3  
Packing group : II  
Environmental hazards : -  
Special precautions for user : Yes  
Remarks : -

### 14.2 IMDG-Code

UN number : 1263  
UN proper shipping name : Paint-related materials  
Transport hazard class(es) : 3  
Packing group : II  
Environmental hazards : -  
Marine pollutant : No  
EmS Code : -

# SAFETY DATA SHEET

## IGL COATINGS™ ECOCOAT WINDOW E1

Material no.

Specification

154287

Revision date

16.02.2021

Version

1.15

Page

6 of 6



### 15. REGULATORY INFORMATION

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### US Federal Regulations

###### US. Toxic Substances Control Act (TSCA)

All chemical substances in this material are included on the TSCA Inventory of Chemical Substances.

###### Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) Hazardous Substance List

None present or none present in regulated quantities.

###### Superfund Amendments and Reauthorization Act of 1986 (SARA)

###### Emergency Planning and Community Right-To-Know Act (EPCRA) Section 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

###### Emergency Planning and Community Right-To-Know Act (EPCRA) Section 313 Toxics Release Inventory (TRI) Reporting

None present or none present in regulated quantities.

###### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

##### US. State Regulation

###### US. California Proposition 65

No ingredient requiring a warning under CA Prop 65.

##### EU Regulation

###### EU. Directive 2012/18/EU (SEVESO III) on Major Accident Hazards Involving Dangerous Substances, Annex I:

Not applicable.

#### 15.2. Chemical safety assessment

No chemical safety assessment is required for this product.

### 16. OTHER INFORMATION

#### Further information

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material use in combination with any other materials or any process, unless specified in the test.

# SAFETY DATA SHEET

## IGL COATINGS™ ECOCOAT WINDOW E2



Material no.

Specification

154322

Revision date

16.02.2021

Version

1.15

Page

1 of 7

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME : IGL Coatings™ ecocoat window E2  
FUNCTION : Hydro- & oleophobic and easy clean agent surface modifier for glass and glazed ceramic  
COMPANY : Ominent Sdn Bhd  
ADDRESS : No.7, Jalan Majistret U1/26, Hicom-Glenmarie Industrial Park, Seksyen U1, 40150 Shah Alam, Selangor.  
PHONE : +60355690980  
EMAIL ADDRESS : regulations@iglcoatings.com

### 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

Regulation (EC) No. 1272/2008

##### Physical hazards

Flammable liquids Category 2

##### Health hazards

Skin Corrosion/Irritation Category 3

Serious Eye Damage/Eye Irritation Category 2A

Specific Target Organ Toxicity-Single Exposure Category 3

##### Target Organs

Narcotic effect

#### 2.2 Label Elements

Regulation (EC) No. 1272/2008



GHS02



GHS07

##### Signal word

Danger

##### Hazard statements

H225 Highly flammable liquid and vapour

H316 Causes mild skin irritation

H319 Causes serious eye irritation

H336 May cause drowsiness or dizziness

##### Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233 Keep container tightly closed.

P235 Keep cool.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical equipment.

P261 Avoid breathing mist or vapours.

P264 Wash thoroughly after handling.

P271 Use only outdoor or in a well-ventilated area.

P280 Wear protective glove, protective clothing, eye protection and face mask.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.



# SAFETY DATA SHEET

## IGL COATINGS™ ECOCOAT WINDOW E2

Material no.

Specification

Version

154322

1.15

Revision date

Page

16.02.2021

2 of 7



P501

Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS No.	Chemical Name			Quantity
	EC No.	Index No.	REACH No.	
	Classification according to Regulation (EC) No. 1272/2008 (CLP)			
67-63-0	Isopropyl alcohol			80-100%
	200-661-7	603-117-00-0	01-2119457558-25-0000	
	Flam. Liq. 2: H225; Eye Irr. 2: H319; STOT SE 3: H336			
7647-01-0	Hydrochloric acid			0.1-1%
	231-595-7	017-002-00-2	01-2119484862-27-0000	
	Skin Corr. 1A: H314; Acute Tox. 3: H331			

#### Additional information:

The exact percentage of some ingredients used in this product are considered to be proprietary and are withheld as confidential business information.

### 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

##### General Information

Remove contaminated or saturated clothing.

##### After Inhalation

Following the inhalation of aerosols or mist: Move victims to fresh air.

If symptoms persist, consult a physician for treatment.

##### After skin contact

Wash off immediately with plenty of water. Consult a doctor in the event of permanent skin irritation.

##### After contact with eyes

Keeping eyelid open, immediately rinse thoroughly for at least 5 minutes using plenty of water or if necessary, eye rinsing solution. Remove contact lenses, if presence and easy to do.

In case of persistent discomfort: Consult an ophthalmologist.

##### After ingestion

Have the mouth rinse with water. Have patient drink plenty of water in small sips. Obtain medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

#### 4.3. Indication of any immediate medical attention and special treatment needed

If required, therapy of irritative effect. After absorbing large amounts of substance: administration of activated charcoal. Acceleration of gastrointestinal passage

### 5. FIRE-FIGHTING MEASURES

#### 5.1 Suitable extinguishing media

Water spray, fog, alcohol resistant foam, CO<sub>2</sub> or dry chemical.

#### 5.2 Unsuitable extinguishing media

No data available.

#### 5.3 Special hazards arising from the substance or mixture

In case of fire cool endangered containers with water. Closed container may rupture if strongly heated.

#### 5.4 Advise for firefighters

Water used to extinguish fire should not enter drainage systems, soil or stretches of water.

Ensure there are sufficient retaining facilities for water used to extinguish fire.

Fire residues and contaminated fire extinguishing water must be disposed of on accordance with local regulations.

#### 5.5 Special protective equipment for fire-fighters

In case of fire: Wear a self-contained respiratory apparatus.

### 6. ACCIDENTAL RELEASE MEASURES



# SAFETY DATA SHEET

## IGL COATINGS™ ECOCOAT WINDOW E2

Material no.

Specification

Version

154322

1.15

Revision date

Page

16.02.2021

3 of 7



### 6.1 Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment (refer to section 8). Ensure adequate ventilation.

### 6.2 Environmental precautions

Do not allow entrance in sewage water, soil stretches of water, groundwater and drainage systems.

### 6.3 Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Fill into marked, sealable containers. To be disposed of in compliance with existing regulation.

Suitable absorbents: diatomaceous earth universal absorbent.

### 6.4 Reference to other sections

Safe handling: Refer to section 7

Personal protection equipment: Refer to section 8

Disposal: Refer to section 13

## 7. HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Provide good ventilation or extraction. Avoid contact with skin and eyes. Handle in accordance with good industrial hygiene and safety practice. The personal protective equipment used must meet the requirements of Regulation (EU) 2016/425 and amendments (CE certification). If workplace exposure limits are exceeded and/or larger amounts are released (leakage, spilling, dust) the indicated respiratory protection should be used. If there is the possibility of skin/eye/body protection should be used. Do not breathe in vapours or aerosols.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Advice on protection against fire and explosion

Take precautionary measures against static charges, keep away from sources of ignition.

Danger of explosion from residual product fumes; therefore, avoid spark production through cutting, grinding, or welding work in the area of the container.

#### Storage

Keep containers tightly closed in a cool, well-ventilated place. Protect from moisture.

### 7.3 Specific end use(s): Refer to section 1.

## 8. EXPOSURE CONTROL/PERSONAL PROTECTION

### 8.1 Control parameters

#### Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

**Additional Information:** The lists valid during the making were used as basis.

### 8.2 Exposure Control

#### 8.2.1 General protective and hygienic measures:

Wash hands before breaks and at the end of work.

#### 8.2.2 Personal protective equipment:

##### Respiratory protection

In case of dusts/vapours/aerosols being formed or if the limit values like TLV are exceeded: use respiratory equipment with suitable filter (filter type ABEK) or wear a self-contained respiratory apparatus. Use only respiratory protection equipment with CE-symbol including four-digit test number. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used. Note time limit for wearing respiratory protective equipment.

##### Hand protection

Glove material : Butyl-rubber

Break through time : >= 480 min

Glove material : Fluorinated rubber (Viton)

Break through time : >= 480 min

Additional information: Selection of protective gloves to meet the requirements of specific workplaces. Suitability for specific workplaces should be clarified with protective glove manufacturers. The information is based on our

# SAFETY DATA SHEET

## IGL COATINGS™ ECOCOAT WINDOW E2



Material no.

Specification

154322

Revision date

16.02.2021

Version

1.15

Page

4 of 7

own tests, references from the literature and information from glove manufacturers, or derived by analogy with similar materials. Please observe that the daily duration of usage of a chemical protective glove is in practice far shorter due to the many influencing factors (e.g. temperature, mechanical strain on the glove material) than the permeation time determined acc. EN 374.

### Eye protection

Safety glasses

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point	: >35 °C
Melting Point	: No data available.
Flash Point	: 14 °C (Method: DIN EN ISO 13736)
Evaporation rate	: No data available.
Flammability Limit-Lower	: 2 % (V) Tested substance: 2-propanol
Flammability Limit-Upper	: 12 % (V) Tested substance: 2-propanol
Vapour pressure	: No data available.
Density	: 0.89 g/cm <sup>3</sup> (20 °C) (Method: DIN 51757)
pH	: 2.1 (1000g/l, 20 °C)
Solubility in Water	: Miscible
Viscosity, dynamic	: approx. 3.7 mPa.s (20 °C, Method: DIN 53015)
Appearance (colour)	: Colourless
Appearance (form)	: Liquid
Odour	: Specific

## 10. STABILITY AND REACTIVITY

**10.1 Reactivity:** No dangerous reaction known under conditions of normal use.

**10.2 Chemical stability:** Stable under recommended storage conditions.

Thermal decomposition / conditions to avoid: No decomposition if used according to specifications.

**10.3 Possibility of hazardous reactions:** Reacts violently with strong oxidants.

**10.4 Conditions to avoid:** Keep away from heat, open flames and other ignition sources.

Formation of flammable or explosive vapour/air mixtures possible.

**10.5 Incompatible materials:** Strong oxidizing agents.

**10.6 Hazardous decomposition products:** None known.

## 11. TOXICOLOGICAL INFORMATION

### Information on toxicological effects

Exposure route	Endpoint	Value	Species	Source
Oral	LD50	5899 mg/kg	Rat	ECHA
Inhalation	LC50	27.1 mg/L	Rat	ECHA

**Skin corrosion/irritation:** No data available.

#### Specified substances:

Propan-2-ol : Not irritating

Hydrochloric acid : OECD Test Guideline 431 (Rabbit): Corrosive, <3 min Corrosive

**Eye irritation:** No data available.

#### Specified substances:

Propan-2-ol : Rabbit-Irritating

**Respiratory or skin sensitization:** No data available.

#### Specified substances:

Propan-2-ol : Buehler Test (Guinea Pig): Not a skin sensitizer. Literature

Hydrochloric acid : Test were not performed due to pH level.

: Maximization test, OECD Test Guideline 406 (Guinea Pig): Not a skin sensitizer.

**Carcinogenicity:** No data available.

# SAFETY DATA SHEET

## IGL COATINGS™ ECOCOAT WINDOW E2



Material no.

Specification

154322

Revision date

16.02.2021

Version

1.15

Page

5 of 7

### Specified substances:

Propan-2-ol : Not classified.

Hydrochloric acid : An expert judgement stated that no classification is necessary based on present knowledge.

### Germ Cell Mutagenicity:

#### In vitro:

#### Specified substances:

Propan-2-ol : Ames test: No evidence of mutagenic effects literature.

Hydrochloric acid : Test for mutagenic potential with various end points: Positive and negative test results

#### In vivo:

#### Specified substances:

Hydrochloric acid : Tests were not performed due to the pH level.

### Specific target organ toxicity – single exposure

Product : May cause drowsiness or dizziness. Narcotic effect.

### Specific target organ toxicity – repeated exposure

#### Specified substances:

Propan-2-ol : Inhalation – vapor: Central nervous system; not classified.

**Aspiration hazard:** No data available.

## 12. ECOLOGICAL INFORMATION

### 12.1 Toxicity

**Specified substances:** Isopropyl alcohol

Endpoint	Value	Species	Exposure time	Sources
LC50	9.64 g/L	Freshwater fish	4 days	ECHA
LC50	10 g/L	Freshwater invertebrates	24 hours	ECHA
EC50	9.17 g/L	Freshwater algae	-	ECHA

**Specified substances:** Hydrochloric acid

Endpoint	Value	Species	Exposure time	Sources
LC50	20.5 mg/L	Freshwater fish	Short-term	ECHA
LC50	450 µg/L	Freshwater invertebrates	Short-term	ECHA
EC50	730 µg/L	Freshwater algae	-	ECHA

### 12.2 Process of degradability

No data available.

### 12.3 Bioaccumulative potential

No data available.

### 12.4 Mobility in soil

No data available.

### 12.5 Results of PBT and vPvB Assessment

Data are not available.

### 12.6 Other adverse effects

An expert Judgement stated that no classification is necessary based on present knowledge.

## 13. DISPOSAL CONSIDERATION

### 13.1 Waste treatment methods

With respect to local regulations, e.g. dispose to suitable waste incineration plant.

#### Uncleaned packaging

Do not reuse empty containers and dispose of in accordance with the regulations issued by the appropriate local authorities.

Incorrect disposal or reuse of this container is illegal and can be dangerous.

If there is product residue in the emptied container, follow directions for handling on the container's label.

Other countries: observe the national regulations.

# SAFETY DATA SHEET

## IGL COATINGS™ ECOCOAT WINDOW E2



Material no.

Specification

154322

Revision date

16.02.2021

Version

1.15

Page

6 of 7

### 13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

### 13.3 Remarks

Do not discharge into surface water. Obtain the consent of pollution control authorities before discharging to wastewater treatment plants. Please consider the relevant national or regional provisions.

## 14. TRANSPORT INFORMATION

### 14.1 IATA-DGR

UN number : 1263  
UN proper shipping name : Paint-related materials  
Transport hazard class(es) : 3  
Packing group : II  
Environmental hazards : No  
Special precautions for user : -  
Remarks : -

### 14.2 IMDG-Code

UN number : 1263  
UN proper shipping name : Paint-related materials  
Transport hazard class(es) : 3  
Packing group : II  
Environmental hazards : No  
Marine pollutant : No  
EmS Code : -

## 15. REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### US Federal Regulations

##### US. Toxic Substances Control Act (TSCA)

All chemical substances in this material are included on the TSCA Inventory of Chemical Substances.

##### Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) Hazardous Substance List

This product contains the following substance subject to the CERCLA Hazardous Substance List

Component	CAS No.
Hydrochloric acid	7647-01-0

##### Superfund Amendments and Reauthorization Act of 1986 (SARA)

##### Emergency Planning and Community Right-To-Know Act (EPCRA) Section 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

##### Emergency Planning and Community Right-To-Know Act (EPCRA) Section 313 Toxics Release Inventory (TRI) Reporting

This product contains the following substance subject to the reporting requirements of EPCRA Section 313

Component	CAS No.
Isopropyl alcohol	67-63-0

##### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

### US. State Regulation

# SAFETY DATA SHEET

## IGL COATINGS™ ECOCOAT WINDOW E2



Material no.

Specification

Version

154322

1.15

Revision date

Page

16.02.2021

7 of 7

### US. California Proposition 65

No ingredient requiring a warning under CA Prop 65.

### EU Regulation

**EU. Directive 2012/18/EU (SEVESO III) on Major Accident Hazards Involving Dangerous Substances, Annex I:**

Not applicable.

### 15.2. Chemical safety assessment

No chemical safety assessment is required for this product.

---

## 16. OTHER INFORMATION

### Further information

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material use in combination with any other materials or any process, unless specified in the test.